

# Ventil-Steckverbinder

## Valve-Connectors

### DIN 43650 C



#### Rectangular Connectors and Cables, GDM-Series, Form C

Valve Connector Cordsets, Field Attachable Rectangular Connectors, Appliance Connectors according to DIN EN 175 301-803

##### VCD 1D-3-3



#### Valve connector

Actuator cordset, single-ended, valve connector according to DIN EN 175 301-803, form C (8.0 mm), without circuitry, 2 + earth connection, connected protective earth

Outer jacket material:  
212 = PVC

Type	Order No.
VCD 1D-3-3-212/2 M	12281
VCD 1D-3-3-212/5 M	12282
VCD 1D-3-3-212/10 M	39149

##### GDSN 207



Field attachable rectangular connector, with central screw M 2.5x27, 2 poles + PE, screw joint for cable PG 7, Standard DIN EN 175 301-803-C

Type	Order No.
GDSN 207 black	933 137-100
GDSN 207 grey	933 137-106

##### GDSN 307



Field attachable rectangular connector, with central screw M 2.5x27, 3 poles + PE, screw joint for cable PG 7, Standard DIN EN 175 301-803-C

Type	Order No.
GDSN 307 black	933 023-100
GDSN 307 grey	933 023-106

##### GSSNA 200 black



Appliance connector with central nut and 2 screws M 2.5x8, 2 poles + PE, Standard DIN EN 175 301-803-C

Type	Order No.
GSSNA 200 black	933 110-100

##### GSSNA 300 black



Appliance connector with central nut and 2 screws M 2.5x8, 3 poles + PE, Standard DIN EN 175 301-803-C

Type	Order No.
GSSNA 300 black	933 111-100

##### GSSNR 200 black



Appliance connector with central nut, version for molding or gasket, 2 poles + PE, Standard DIN EN 175 301-803-C

Type	Order No.
GSSNR 200 black	933 113-100

##### GSSNR 300 black



Appliance connector with central nut, version for molding or gasket, 3 poles + PE, Standard DIN EN 175 301-803-C

Type	Order No.
GSSNR 300 black	933 112-100

## Rectangular Connectors and Cables, GDM-Series, Form C

Valve Connector Cordsets – Single-ended, Field Attachable Rectangular Connectors, Appliance Connectors, Industry Standard

### VC 1A-1-3



#### Valve connector

Actuator cordset, single-ended, valve connector similar to DIN EN 175 301-803, industry standard form C (9.4 mm), with LED function indicator, varistor voltage protection, connected protective earth

#### Outer jacket material:

212 = PVC  
226 = PUR halogen-free, black

Type	Order No.
VC 1A-1-3-212/2 M	12263
VC 1A-1-3-212/5 M	12264
VC 1A-1-3-212/10 M	46944
VC 1A-1-3-226/2 M	43906
VC 1A-1-3-226/5 M	43909
VC 1A-1-3-226/10 M	43905

### VC 1D-3-3



#### Valve connector

Actuator cordset, single-ended, valve connector similar to DIN EN 175 301-803, industry standard form C (9.4 mm), without circuitry, 2 + earth connection, connected protective earth

#### Outer jacket material:

212 = PVC

Type	Order No.
VC 1D-3-3-212/2 M	12265
VC 1D-3-3-212/5 M	12266
VC 1D-3-3-212/10 M	16217

### GDS 207



Field attachable rectangular connector, with central screw M 3x28, 2 poles + PE, screw joint for cable PG 7, industry standard (9.4 mm)

Type	Order No.
GDS 207 black	933 138-100
GDS 207 grey	933 138-106

### GDS 307



Field attachable rectangular connector, with central screw M 3x28, 3 poles + PE, screw joint for cable PG 7, industry standard (9.4 mm)

Type	Order No.
GDS 307 black	933 024-100
GDS 307 grey	933 024-106

### GSSA 200 black



Appliance connector with central nut and 2 screws M 3x8, 2 poles + PE, industry standard (9.4 mm)

Type	Order No.
GSSA 200 black	933 117-100

### GSSA 300 black



Appliance connector with central nut and 2 screws M 3x8, 3 poles + PE, industry standard (9.4 mm)

Type	Order No.
GSSA 300 black	933 116-100

### GSSR 200 black



Appliance connector with central nut, version for molding or gasket, 2 poles + PE, industry standard (9.4 mm)

Type	Order No.
GSSR 200 black	933 115-100

### GSSR 300 black



Appliance connector with central nut, version for molding or gasket, 3 poles + PE, industry standard (9.4 mm)

Type	Order No.
GSSR 300 black	933 114-100

Werner Wirth GmbH

Hellgrundweg 111  
22525 Hamburg  
Germany

Tel +49 (0)40 752 491-0  
Fax +49 (0)40 752 491-91

info@wernerwirth.de  
www.wernerwirth.de



**WERNER  
WIRTH**

PROJECT | CONNECT | PROTECT